

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
15 September 2005 (15.09.2005)

PCT

(10) International Publication Number
WO 2005/085657 A1

(51) International Patent Classification: **F16B 5/02**,
12/18, 12/32, 37/00, A47B 47/04, B25B 5/10, B04B 1/61

(21) International Application Number:
PCT/AU2005/000282

(22) International Filing Date: 28 February 2005 (28.02.2005)

(23) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
2004901112 3 March 2004 (03.03.2004) AU
2004903527 28 June 2004 (28.06.2004) AU

(71) Applicant (for all designated States except US): **RAPID-JOINT PTY LTD** [AU/AU]; Factory 17 Grace Avenue, Warrnambool, VIC 3280 (AU).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **DORNEY, Jarrud,**


Leigh [AU/AU]; 2 Ferrier Drive, Warrnambool, VIC 3280 (AU). **VAN DE LOO, Paul** [AU/AU]; Lot 26, Moores Road, Norton Summit, S.A. 5136 (AU). **GRANSHURY, Kenneth** [AU/AU]; 14 Gurus Road, Kensington Park, S.A. 5068 (AU).

(74) Agent: **WATERMARK PATENT & TRADEMARK ATTORNEYS**; 290 Burwood Road, Hawthorn, VIC 3122 (AU).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(Continued on next page)

(54) Title: **IMPROVEMENTS IN CLAMPING ASSEMBLIES**



(57) Abstract: A self-aligning coupling device (400) for installation in channel having an open end and a pair of substantially parallel side walls. The device includes an elongate connecting portion (402) having a longitudinal axis (404), a channel abutment portion (408), and at least one laterally projecting lug (412, 414). In use, the coupling device (400) is installed in the channel with the channel abutment portion (408) located at least partially within the channel and the laterally projecting lug (412, 414) located outside the open end of the channel. The channel abutment portion (408) is formed such that when aligned in a first angular position within the channel it abuts the side walls of the channel to prevent rotation of the device in a first rotational direction about said longitudinal axis, while allowing rotation in a second, opposed rotational direction.

WO 2005/085657 A1